



**ASSY POSITIONS**  
(FACING DRIVE END)

**APPROX. WEIGHTS**

PUMP ASSY - DRY	LBS. [KG]
IMPELLER/SHAFT ASSY	7500 [3400]
HOUSING*	2800 [1270]
HEADS/CONE ASSY (EA.)*	1460 [660]
	1560 [710]

\* COMPONENTS ARE IRON. FOR S/STL ADD 13%.

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF VOONER FLOGARD CORPORATION, CHARLOTTE, NC 28273 U.S.A. WRITTEN PERMISSION MUST BE OBTAINED FROM VOONER FLOGARD CORPORATION, TO DISCLOSE TO OTHERS ANY INFORMATION CONTAINED HEREON. THIS DOCUMENT, AND COPIES THEREOF, ARE SUBJECT TO IMMEDIATE RETURN TO VOONER FLOGARD CORPORATION ON REQUEST.

- GENERAL NOTES:**
- 1) PRIMARY DIMENSIONS ARE IN INCHES. [mm]
  - 2) FLANGES TO DIN P10 BOLT PATTERNS AND THICKNESS. BOLT HOLES STRADDLE CENTER LINES.
  - 3) PIPE THD. CONNECTIONS ARE ANSI B2.1.



**VOONER FLOGARD CORPORATION**  
CHARLOTTE, NC 28273

**OUTLINE DRAWING**  
V4L50 DIN

SIZE	FSCM NO.	DWG NO.	REV
A	NONE	V4L50 DIN	B

Scale: none      2/26/08      Sheet: 1 of 1