


PUMP FOOTING



ASSY POSITIONS
(FACING DRIVE END)

GENERAL NOTES:
 1) PRIMARY DIMENSIONS ARE IN INCHES. [mm]
 2) FLANGES TO ANSI B16.5 CLASS 125
 BOLT PATTERNS AND THICKNESS. BOLT
 HOLES STRADDLE CENTER LINES.
 3) PIPE THD. CONNECTIONS ARE ANSI B2.1.

| APPROX. WEIGHTS | LBS. [Kg] |
|------------------------|-------------|
| PUMP ASSY - DRY | 8350 [3790] |
| IMPELLER/SHAFT ASSY | 3358 [1520] |
| HOUSING* | 1742 [790] |
| HEADS/CONE ASSY (EA.)* | 1560 [710] |

* COMPONENTS ARE IRON. FOR S/STL ADD 13%.

| | | | |
|----------------------------------|-------------------------|---|-----------------|
| | | VOONER FLOGARD CORPORATION CHARLOTTE, NC 28273 | |
| OUTLINE DRAWING V4M55 | | | |
| SIZE A | FSCM NO. NONE | DWG NO. V4M55 | REV B |
| Scale: none | | 2/26/08 | Sheet: 1 of 1 |

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF VOONER FLOGARD CORPORATION, CHARLOTTE, NC, 28273 U.S.A. WRITTEN PERMISSION MUST BE OBTAINED FROM VOONER FLOGARD CORPORATION, TO DISCLOSE TO OTHERS ANY INFORMATION CONTAINED HEREON. THIS DOCUMENT, AND COPIES THEREOF, ARE SUBJECT TO IMMEDIATE RETURN TO VOONER FLOGARD CORPORATION ON REQUEST.