



ASSY POSITIONS
(FACING DRIVE END)

- GENERAL NOTES:**
- 1) PRIMARY DIMENSIONS ARE IN INCHES. [mm]
 - 2) FINISHES TO DIM F10
 - 3) BOLT PATTERNS AND PATTERN THICKNESS. BOLT
 - 4) BOLT PATTERNS AND PATTERN THICKNESS. BOLT
 - 5) PIPE CONNECTIONS ARE MET B2.1.
 - 6) SHROUD VENT RIDING FURNISHED ONLY ON "M" AND "H" MODELS.

APPROX. WEIGHTS

	LBS. [kg]
PUMP ASSY - DRY	1475 [669]
IMPELLER/SHAFT ASSY	428 [194]
HOUSING*	309 [140]
HEADS (EA.)*	265 [120]
CONES (EA.)*	35 [16]
BEARING CARRIER (EA)	35 [16]

PUMP FOOTING

* COMPONENTS ARE IRON. FOR S/STL ADD 13%.

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF YOONER FLOGARD CORPORATION, CHARLOTTE, NC, 28273 U.S.A. WRITTEN PERMISSION MUST BE OBTAINED FROM YOONER FLOGARD CORPORATION TO DISCLOSE TO OTHERS ANY INFORMATION CONTAINED HEREON. THIS DOCUMENT, AND COPIES THEREOF, ARE SUBJECT TO IMMEDIATE RETURN TO YOONER FLOGARD CORPORATION ON REQUEST.

<p>Vodner Flogard VOONER FLOGARD CORPORATION CHARLOTTE, NC 28273</p>			
SIZE	FSCM NO.	DWG NO.	REV
A	NONE	VG10 DIN	A
Scale: none		9/24/07	Sheet 1 of 1