



ASSY POSITIONS
(FACING DRIVE END)

- GENERAL NOTES:**
- 1) DIMENSIONS ARE IN INCHES. [mm]
 - 2) DIMENSIONS TO CENTER UNLESS NOTED OTHERWISE.
 - 3) PIPE THD. CONNECTIONS ARE ANSI B2.1.
 - 4) SHROUD VENT PIPING FURNISHED ONLY ON "M" AND "H" MODELS.

APPROX. WEIGHTS

COMPONENT	LBS. [kg]
PUMP ASSY - DRY	3285 [1490]
IMPELLER/SHAFT ASSY	952 [432]
HOUSING*	816 [370]
HEADS (EA.)*	529 [240]
CONES (EA.)*	82 [37]
BEARING CARRIER (EA)	49 [22]

PUMP FOOTING

* COMPONENTS ARE IRON, FOR S/STL ADD 13%.

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF VOONER FLOGARD CORPORATION, CHARLOTTE, NC 28273 U.S.A. WRITTEN PERMISSION MUST BE OBTAINED FROM VOONER FLOGARD CORPORATION TO DISCLOSE TO OTHERS ANY INFORMATION CONTAINED HEREON. THIS DOCUMENT, AND COPIES THEREOF, ARE SUBJECT TO IMMEDIATE RETURN TO VOONER FLOGARD CORPORATION ON REQUEST.



VOONER FLOGARD CORPORATION
CHARLOTTE, NC 28273

OUTLINE DRAWING
VG20 DIN

SIZE	FSCM NO.	DWG NO.	REV
A	NONE	VG20 DIN	B

Scale: none 9/24/07 Sheet: 1 of 1