

ASSY POSITIONS
(FACING DRIVE END)


GENERAL NOTES:
1) PRIMARY DIMENSIONS ARE IN INCHES. [mm]
2) FLANGES TO ANSI B16.5 CLASS 125
BOLT PATTERNS AND THICKNESS, BOLT
HOLES STRADDLE CENTER LINES.
3) PIPE THD. CONNECTIONS ARE ANSI B2.1.
4) SHROUD VENT PIPING FURNISHED ONLY ON
"-M" AND "-H" MODELS.

APPROX. WEIGHTS

	LBS. [KG]
PUMP ASSY - DRY	8850 [4014]
IMPELLER/SHAFT ASSY	2646 [1200]
HOUSING*	1894 [859]
HEADS (EA.)*	1279 [580]
CONES (EA.)*	220 [100]
BEARING CARRIER (EA)	106 [48]

* COMPONENTS ARE IRON. FOR S/STL ADD 13%.

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF VOONER FLOGARD CORPORATION, CHARLOTTE, NC, 28273 U.S.A. WRITTEN PERMISSION MUST BE OBTAINED FROM VOONER VACUUM PUMPS, INC. TO DISCLOSE TO OTHERS ANY INFORMATION CONTAINED HEREON. THIS DOCUMENT, AND COPIES THEREOF, ARE SUBJECT TO IMMEDIATE RETURN TO VOONER VACUUM PUMPS, INC. ON REQUEST.



Vooner Flogard
VOONER FLOGARD CORPORATION
CHARLOTTE, NC 28273

OUTLINE DRAWING
VG40 DIN

SIZE	FSCM NO.	DWG NO.	REV
A	NONE	VG40 DIN	C

Scale: none Date: 2/26/08 Sheet: 1 of 1