



Date: 2/1/09

Supersedes: New

**TECHNICAL DATA SHEET**

**VOONER TWO STAGE LIQUID RING VACUUM PUMP**

Specified, constructed, tested, and guaranteed by:

**Vooner FloGard® Corporation**

P.O. Box 240360, Charlotte, NC 28224-0360  
4729 Stockholm Court, Charlotte, NC 28273

Telephone: (704) 552-9314  
Toll Free: 1-800-345-7879  
Telefax: (704) 554-8230

**Model: VTS10**

Type: Two rotors, cone shape ports, liquid ring vacuum pump

Sealing liquid flow rate nominal: 25-35 gpm (95-130 lpm)  
 Sealing liquid connection: 1" NPT  
 Shaft sealing: Packing  
 Bearing design: Double row spherical roller bearing, external, grease lubricated, Type: NSK 22315EAE4/22317EAE4  
 Shaft diameter, drive end: 2¾"  
 Pump flange connections: 6" inlet, 5" outlet  
 Approximate pump weight: 2,390 lbs. (1,084 kg)

**MATERIAL CONSTRUCTION FEATURES**

<b>Model</b>	<b>Rotors</b>	<b>Cones</b>	<b>Heads</b>	<b>Bearing Carrier</b>	<b>Housing</b>	<b>Shaft</b>	<b>Packing Gland, Studs, Nuts</b>
A	Ductile Iron	Cast Iron	Cast Iron	Carbon Steel	Cast Iron	Carbon Steel	316 SS
K	304 SS	Cast Iron	Cast Iron	Carbon Steel	Cast Iron	Carbon Steel	316 SS

(SS - cast stainless steel)